

Product Name: GASOLINE, UNLEADED AUTOMOTIVE
Revision Date: 03 Sep 2020
Page 1 of 16

SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: GASOLINE, UNLEADED AUTOMOTIVE
Product Description: Hydrocarbons and Additives
Product Code: 123455-20
Intended Use: Fuel, Gasoline

Trade Names	Trade Names
ESSO EXTRA MIDGRADE UNLEADED	ESSO MIDGRADE UNLEADED
ESSO PREMIUM UNLEADED	ESSO REGULAR UNLEADED
ESSO SUPER PREMIUM UNLEADED	EXXON MIDGRADE UNLEADED
EXXON PREMIUM UNLEADED	EXXON REGULAR UNLEADED
EXXON SYNERGY EXTRA GASOLINE	EXXON SYNERGY REGULAR GASOLINE
EXXON SYNERGY SUPREME+™ PREMIUM GASOLINE	GASOLINE
INDOLENE GASOLINE	MIDGRADE UNLEADED
MOBIL EXTRA UNLEADED	MOBIL REGULAR UNLEADED
MOBIL SPECIAL UNLEADED	MOBIL SUPER UNLEADED
MOBIL SYNERGY EXTRA GASOLINE	MOBIL SYNERGY REGULAR GASOLINE
MOBIL SYNERGY SUPREME+™ PREMIUM GASOLINE	PREMIUM UNLEADED
REGULAR UNLEADED	SYNERGY EXTRA GASOLINE
SYNERGY REGULAR GASOLINE	SYNERGY SUPREME+™ PREMIUM GASOLINE
UNLEADED GASOLINE	

COMPANY IDENTIFICATION

Supplier: EXXON MOBIL CORPORATION
22777 Springwoods Village Parkway
Spring, TX 77389 USA
24 Hour Health Emergency 609-737-4411
Transportation Emergency Phone 800-424-9300 or 703-527-3887 CHEMTREC
Product Technical Information 800-662-4525
MSDS Internet Address www.exxon.com, www.mobil.com

SECTION 2 HAZARDS IDENTIFICATION

This material is hazardous according to regulatory guidelines (see (M)SDS Section 15).

CLASSIFICATION:

Flammable liquid: Category 1.
Skin irritation: Category 2. Germ Cell Mutagen: Category 1B. Carcinogen: Category 1B. Specific target organ toxicant (central nervous system): Category 3. Aspiration toxicant: Category 1.

LABEL:

Pictogram:

Product Name: GASOLINE, UNLEADED AUTOMOTIVE

Revision Date: 03 Sep 2020

Page 2 of 16



Signal Word: Danger

Hazard Statements:

H224: Extremely flammable liquid and vapor. H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H336: May cause drowsiness or dizziness. H340: May cause genetic defects. H350: May cause cancer.

Precautionary Statements:

P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use. P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P210: Keep away from heat/sparks/open flames/hot surfaces. -- No smoking. P233: Keep container tightly closed. P240: Ground / bond container and receiving equipment. P241: Use explosion-proof electrical, ventilating, and lighting equipment. P242: Use only non-sparking tools. P243: Take precautionary measures against static discharge. P261: Avoid breathing mist / vapours. P264: Wash skin thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. P273: Avoid release to the environment. P280: Wear protective gloves/protective clothing/eye protection/face protection. P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308 + P313: IF exposed or concerned: Get medical advice/ attention. P312: Call a POISON CENTER or doctor/physician if you feel unwell. P331: Do NOT induce vomiting. P332 + P313: If skin irritation occurs: Get medical advice/ attention. P362 + P364: Take off contaminated clothing and wash it before reuse. P370 + P378: In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish. P391: Collect spillage. P403 + P235: Store in a well-ventilated place. Keep cool. P405: Store locked up. P501: Dispose of contents and container in accordance with local regulations.

Contains: GASOLINE

Other hazard information:

HAZARD NOT OTHERWISE CLASSIFIED (HNOC): None as defined under 29 CFR 1910.1200.

PHYSICAL / CHEMICAL HAZARDS

Material can accumulate static charges which may cause an ignition. Material can release vapors that readily form flammable mixtures. Vapor accumulation could flash and/or explode if ignited.

HEALTH HAZARDS

High-pressure injection under skin may cause serious damage. May be irritating to the eyes, nose, throat, and lungs. Exposure to benzene is associated with cancer (acute myeloid leukemia and myelodysplastic syndrome), damage to the blood-producing system, and serious blood disorders (see Section 11).

Product Name: GASOLINE, UNLEADED AUTOMOTIVE
Revision Date: 03 Sep 2020
Page 3 of 16

ENVIRONMENTAL HAZARDS

Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

NFPA Hazard ID: Health: 1 Flammability: 4 Reactivity: 0
HMIS Hazard ID: Health: 1* Flammability: 4 Reactivity: 0

NOTE: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

This material is defined as a mixture.

Hazardous Substance(s) or Complex Substance(s) required for disclosure

Name	CAS#	Concentration*	GHS Hazard Codes
ETHYL ALCOHOL	64-17-5	< 11%	H225, H319(2A)
GASOLINE	86290-81-5	89 - 100%	H224, H304, H336, H340(1B), H350(1B), H315, H401, H411

Hazardous Constituent(s) Contained in Complex Substance(s) required for disclosure

Name	CAS#	Concentration*	GHS Hazard Codes
BENZENE	71-43-2	<= 1.65%	H225, H303, H304, H340(1B), H350(1A), H315, H319(2A), H372, H401, H412
ETHYL BENZENE	100-41-4	1 - 5%	H225, H304, H332, H373, H401, H412
N-HEXANE	110-54-3	1 - 5%	H225, H304, H336, H361(F), H315, H373, H401, H411
NAPHTHALENE	91-20-3	<1%	H228(2), H302, H351, H400(M factor 1), H410(M factor 1)
PSEUDOCUMENE (1,2,4-TRIMETHYLBENZENE)	95-63-6	1 - 5%	H226, H304, H332, H335, H315, H319(2A), H401, H411
TOLUENE	108-88-3	5 - 10%	H225, H304, H336, H315, H373, H401, H412
TRIMETHYL BENZENE	25551-13-7	1 - 5%	H226, H302, H312, H315, H319(2A)
XYLENES	1330-20-7	5 - 10%	H226, H303, H304, H312, H332, H335, H315, H320(2B), H373, H401, H412

* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

Product Name: GASOLINE, UNLEADED AUTOMOTIVE

Revision Date: 03 Sep 2020

Page 4 of 16

NOTE: The concentration of the components shown above may vary substantially. In certain countries, benzene content may be limited to lower levels. Oxygenates such as tertiary-amyl-methyl ether, ethanol, di-isopropyl ether, and ethyl-tertiary-butyl ether may be present. Because of volatility considerations, gasoline vapor may have concentrations of components very different from those of liquid gasoline. The major components of gasoline vapor are: butane, isobutane, pentane, and isopentane. The reportable component percentages, shown in the composition/information on ingredients section, are based on API's evaluation of a typical gasoline mixture. Oxygenates may be present up to the maximum permitted by European Standard EN228. Motor gasoline is considered a mixture by EPA under the Toxic Substances Control Act (TSCA). The refinery streams used to blend motor gasoline are all on the TSCA Chemical Substances Inventory.

As per paragraph (i) of 29 CFR 1910.1200, formulation is considered a trade secret and specific chemical identity and exact percentage (concentration) of composition may have been withheld. Specific chemical identity and exact percentage composition will be provided to health professionals, employees, or designated representatives in accordance with applicable provisions of paragraph (i).

SECTION 4

FIRST AID MEASURES

INHALATION

Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device.

SKIN CONTACT

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

Seek immediate medical attention. Do not induce vomiting.

NOTE TO PHYSICIAN

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. This material, or a component, may be associated with cardiac sensitization following very high exposures (well above occupational exposure limits) or with concurrent exposure to high stress levels or heart-stimulating substances like epinephrine. Administration of such substances should be avoided.

SECTION 5

FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Inappropriate Extinguishing Media: Straight Streams of Water

FIRE FIGHTING

Product Name: GASOLINE, UNLEADED AUTOMOTIVE

Revision Date: 03 Sep 2020

Page 5 of 16

Fire Fighting Instructions: Evacuate area. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect personnel attempting to stop a leak. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Unusual Fire Hazards: Extremely Flammable. Vapors are flammable and heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

Hazardous Combustion Products: Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulfur oxides

FLAMMABILITY PROPERTIES

Flash Point [Method]: <-40°C (-40°F) [ASTM D-56]

Flammable Limits (Approximate volume % in air): LEL: 1.4 UEL: 7.6

Autoignition Temperature: >250°C (482°F)

SECTION 6

ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.

PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

For emergency responders: Respiratory protection: half-face or full-face respirator with filter(s) for organic vapor and, when applicable, H₂S, or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to aromatic hydrocarbons are recommended. Note: gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

SPILL MANAGEMENT

Land Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. Large Spills: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Water Spill: Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop

Product Name: GASOLINE, UNLEADED AUTOMOTIVE

Revision Date: 03 Sep 2020

Page 6 of 16

leak if you can do it without risk. Do not confine in area of spill. Advise occupants and shipping in downwind areas of fire and explosion hazard and warn them to stay clear. Allow liquid to evaporate from the surface. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

SECTION 7

HANDLING AND STORAGE

HANDLING

Avoid all personal contact. Prevent exposure to ignition sources, for example use non-sparking tools and explosion-proof equipment. Potentially toxic/irritating fumes/vapors may be evolved from heated or agitated material. Do not siphon by mouth. Use only with adequate ventilation. Do not use as a cleaning solvent or other non-motor fuel uses. For use as a motor fuel only. It is dangerous and/or unlawful to put fuel into unapproved containers. Do not fill container while it is in or on a vehicle. Static electricity may ignite vapors and cause fire. Place container on ground when filling and keep nozzle in contact with container. Do not use electronic devices (including but not limited to cellular phones, computers, calculators, pagers or other electronic devices, etc.) during safety critical tasks, such as bulk fuel loading or unloading operations, or in storage areas where vapors may be present, unless the devices are certified intrinsically safe by an approved national testing agency and to the safety standards required by national and/or local laws and regulations. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or ground procedures. However, bonding and grounds may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

Static Accumulator: This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100×10^{-12} Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.

STORAGE

Ample fire water supply should be available. A fixed sprinkler/deluge system is recommended. The type of container used to store the material may affect static accumulation and dissipation. Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well-ventilated area. Outside or detached storage preferred. Keep away from incompatible materials. Storage containers should be grounded and bonded. Fixed storage containers, transfer containers and associated equipment should be grounded and bonded to prevent accumulation of static charge.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

Product Name: GASOLINE, UNLEADED AUTOMOTIVE

Revision Date: 03 Sep 2020

Page 7 of 16

EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name	Form	Limit / Standard			NOTE	Source
BENZENE		OSHA Action level	0.5 ppm		N/A	OSHA Sp.Reg.
BENZENE		STEL	5 ppm		N/A	OSHA Sp.Reg.
BENZENE		TWA	1 ppm		N/A	OSHA Sp.Reg.
BENZENE		STEL	1 ppm		Skin	ExxonMobil
BENZENE		TWA	0.5 ppm		Skin	ExxonMobil
BENZENE		STEL	2.5 ppm		Skin	ACGIH
BENZENE		TWA	0.5 ppm		Skin	ACGIH
ETHYL ALCOHOL		TWA	1900 mg/m ³	1000 ppm	N/A	OSHA Z1
ETHYL ALCOHOL		STEL	1000 ppm		N/A	ACGIH
ETHYL BENZENE		TWA	435 mg/m ³	100 ppm	N/A	OSHA Z1
ETHYL BENZENE		TWA	20 ppm		N/A	ACGIH
GASOLINE		STEL	200 ppm		N/A	ExxonMobil
GASOLINE		TWA	100 ppm		N/A	ExxonMobil
GASOLINE		STEL	500 ppm		N/A	ACGIH
GASOLINE		TWA	300 ppm		N/A	ACGIH
N-HEXANE		TWA	1800 mg/m ³	500 ppm	N/A	OSHA Z1
N-HEXANE		TWA	50 ppm		Skin	ACGIH
NAPHTHALENE		TWA	50 mg/m ³	10 ppm	N/A	OSHA Z1
NAPHTHALENE		TWA	10 ppm		Skin	ACGIH
PSEUDOCUMENE (1,2,4-TRIMETHYLBENZENE)		TWA	25 ppm		N/A	ACGIH
TOLUENE		Ceiling	300 ppm		N/A	OSHA Z2
TOLUENE		Maximum concentration	500 ppm		N/A	OSHA Z2
TOLUENE		TWA	200 ppm		N/A	OSHA Z2
TOLUENE		TWA	20 ppm		N/A	ACGIH
TRIMETHYL BENZENE		TWA	25 ppm		N/A	ACGIH
XYLENES		TWA	435 mg/m ³	100 ppm	N/A	OSHA Z1
XYLENES		STEL	150 ppm		N/A	ACGIH
XYLENES		TWA	100 ppm		N/A	ACGIH

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

Biological limits

Product Name: GASOLINE, UNLEADED AUTOMOTIVE

Revision Date: 03 Sep 2020

Page 8 of 16

Substance	Specimen	Sampling Time	Limit	Determinant	Source
BENZENE	Creatinine in urine	End of shift	25 ug/g	S-Phenylmercapturic acid	ACGIH BELs (BEIs)
BENZENE	Creatinine in urine	End of shift	500 ug/g	t,t-Muconic acid	ACGIH BELs (BEIs)
ETHYL BENZENE	Creatinine in urine	End of shift	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	ACGIH BELs (BEIs)
N-HEXANE	Urine	End of shift	0.5 mg/l	2,5-Hexanedione, without hydrolysis	ACGIH BELs (BEIs)
NAPHTHALENE	No Biological Specimen provided	End of shift	Not Assigned	1-Naphthol, with hydrolysis + 2-Naphthol, with hydrolysis	ACGIH BELs (BEIs)
TOLUENE	Blood	Prior to last shift of work wk	0.02 mg/l	Toluene	ACGIH BELs (BEIs)
TOLUENE	Creatinine in urine	End of shift	0.3 mg/g	o-Cresol, with hydrolysis	ACGIH BELs (BEIs)
TOLUENE	Urine	End of shift	0.03 mg/l	Toluene	ACGIH BELs (BEIs)
XYLENES	Creatinine in urine	End of shift	1.5 g/g	Methylhippuric acids	ACGIH BELs (BEIs)

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Use explosion-proof ventilation equipment to stay below exposure limits.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

Half-face filter respirator

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Product Name: GASOLINE, UNLEADED AUTOMOTIVE

Revision Date: 03 Sep 2020

Page 9 of 16

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:
Chemical/oil resistant clothing is recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

GENERAL INFORMATION

Physical State: Liquid
Color: Clear (May Be Dyed)
Odor: Petroleum/Solvent
Odor Threshold: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15 °C): 0.74
Density (at 15 °C): 720 kg/m³ (6.01 lbs/gal, 0.72 kg/dm³) - 758 kg/m³ (6.33 lbs/gal, 0.76 kg/dm³)
Flammability (Solid, Gas): N/A
Flash Point [Method]: <-40°C (-40°F) [ASTM D-56]
Flammable Limits (Approximate volume % in air): LEL: 1.4 UEL: 7.6
Autoignition Temperature: >250°C (482°F)
Boiling Point / Range: > 20°C (68°F)
Decomposition Temperature: N/D
Vapor Density (Air = 1): 3 at 101 kPa
Vapor Pressure: > 26.6 kPa (200 mm Hg) at 20 °C
Evaporation Rate (n-butyl acetate = 1): > 10
pH: N/A
Log Pow (n-Octanol/Water Partition Coefficient): > 3
Solubility in Water: Negligible
Viscosity: <1 cSt (1 mm²/sec) at 40 °C
Oxidizing Properties: See Hazards Identification Section.

OTHER INFORMATION

Freezing Point: N/D
Melting Point: N/A

SECTION 10 STABILITY AND REACTIVITY

REACTIVITY: See sub-sections below.

Product Name: GASOLINE, UNLEADED AUTOMOTIVE
Revision Date: 03 Sep 2020
Page 10 of 16

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: Heat, sparks, flame, and build up of static electricity.

MATERIALS TO AVOID: Alkalies, Halogens, Strong Acids, Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization will not occur.

SECTION 11	TOXICOLOGICAL INFORMATION
------------	---------------------------

INFORMATION ON TOXICOLOGICAL EFFECTS

Hazard Class	Conclusion / Remarks
Inhalation	
Acute Toxicity: (Rat) 4 hour(s) LC50 > 5000 mg/m3 (Vapor)	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 403
Irritation: No end point data for material.	Elevated temperatures or mechanical action may form vapors, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs.
Ingestion	
Acute Toxicity (Rat): LD50 > 5000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 401
Skin	
Acute Toxicity (Rabbit): LD50 > 2000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 402
Skin Corrosion/Irritation (Rabbit): Data available.	Irritating to the skin. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 404
Eye	
Serious Eye Damage/Irritation (Rabbit): Data available.	May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 405
Sensitization	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: Data available.	Not expected to be a skin sensitizer. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 406
Aspiration: Data available.	May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material.
Germ Cell Mutagenicity: Data available.	Caused genetic effects in laboratory animals, but the relevance to humans is uncertain. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 471 475 476
Carcinogenicity: Data available.	Caused cancer in laboratory animals. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 451
Reproductive Toxicity: Data available.	Not expected to be a reproductive toxicant. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 416 421
Lactation: No end point data for material.	Not expected to cause harm to breast-fed children.
Specific Target Organ Toxicity (STOT)	

Product Name: GASOLINE, UNLEADED AUTOMOTIVE

Revision Date: 03 Sep 2020

Page 11 of 16

Single Exposure: No end point data for material.	May cause drowsiness or dizziness.
Repeated Exposure: Data available.	Not expected to cause organ damage from prolonged or repeated exposure. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 410 412 453

TOXICITY FOR SUBSTANCES

NAME	ACUTE TOXICITY
ETHYL BENZENE	Inhalation Lethality: 4 hour(s) LC50 17.8 mg/l (Vapor) (Rat); Oral Lethality: LD50 3.5 g/kg (Rat)
NAPHTHALENE	Inhalation Lethality: 4 hour(s) LC50 > 0.4 mg/l (Max attainable vapor conc.) (Rat); Oral Lethality: LD50 533 mg/kg (Mouse)

OTHER INFORMATION**For the product itself:**

Laboratory animal studies have shown that prolonged and repeated inhalation exposure to light hydrocarbon vapors in the same boiling range as this product can produce adverse kidney effects in male rats. However, these effects were not observed in similar studies with female rats, male and female mice, or in limited studies with other animal species. Additionally, in a number of human studies, there was no clinical evidence of such effects at normal occupational levels. In 1991, The U.S. EPA determined that the male rat kidney is not useful for assessing human risk.

Vapor concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic and may have other central nervous system effects.

Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema. Exposure to this material, or one of its components, in situations where there is the potential for high levels, such as in confined spaces or with abuse, may result in abnormal heart rhythm (arrhythmia). High-level exposure to hydrocarbons (above occupational exposure limits) may initiate arrhythmia in a worker that is undergoing stress or is taking a heart-stimulating substance such as epinephrine, a nasal decongestant, or an asthma or cardiovascular drug.

Gasoline unleaded: Caused cancer in animal tests. Chronic inhalation studies resulted in liver tumors in female mice and kidney tumors in male rats. Neither result considered significant for human health risk assessment by the United States EPA and others. Did not cause mutations In Vitro or In Vivo. Negative in inhalation developmental studies and reproductive tox studies. Inhalation of high concentrations in animals resulted in reversible central nervous system depression, but no persistent toxic effect on the nervous system. Non-sensitizing in test animals. Caused nerve damage in humans from abusive use (sniffing).

Contains:

BENZENE: Caused cancer (acute myeloid leukemia and myelodysplastic syndrome), damage to the blood-producing system, and serious blood disorders in human studies. Caused genetic effects and effects on the immune system in laboratory animal and some human studies. Caused toxicity to the fetus and cancer in laboratory animal studies.

ETHANOL: Prolonged or repeated exposure to high concentrations of ethanol vapor or overexposure by ingestion may produce adverse effects to brain, kidney, liver, and reproductive organs, birth defects in offspring, and developmental toxicity in offspring.

NAPHTHALENE: Exposure to high concentrations of naphthalene may cause destruction of red blood cells, anemia, and cataracts. Naphthalene caused cancer in laboratory animal studies, but the relevance of these findings to humans is uncertain.

N-HEXANE: Prolonged and/or repeated exposures to n-Hexane can cause progressive and potentially irreversible damage to the peripheral nervous system (e.g. fingers, feet, arms, legs, etc.). Simultaneous exposure to Methyl Ethyl Ketone (MEK) or Methyl Isobutyl Ketone (MIBK) and n-Hexane can potentiate the risk of adverse effects from n-Hexane on the peripheral nervous system. n-Hexane has been shown to cause testicular damage at high doses in male rats. The relevance of this effect for humans is unknown.

Product Name: GASOLINE, UNLEADED AUTOMOTIVE

Revision Date: 03 Sep 2020

Page 12 of 16

TOLUENE : Concentrated, prolonged or deliberate inhalation may cause brain and nervous system damage. Prolonged and repeated exposure of pregnant animals (> 1500 ppm) have been reported to cause adverse fetal developmental effects.

TRIMETHYLBENZENE: Long-term inhalation exposure of trimethylbenzene caused effects to the blood in laboratory animals.

ETHYLBENZENE: Caused cancer in laboratory animal studies. The relevance of these findings to humans is uncertain.

The following ingredients are cited on the lists below:

Chemical Name	CAS Number	List Citations
BENZENE	71-43-2	1, 3, 6
ETHYL BENZENE	100-41-4	5
GASOLINE	86290-81-5	5
NAPHTHALENE	91-20-3	2, 5

--REGULATORY LISTS SEARCHED--

1 = NTP CARC

3 = IARC 1

5 = IARC 2B

2 = NTP SUS

4 = IARC 2A

6 = OSHA CARC

SECTION 12

ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

ECOTOXICITY

Material -- Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

MOBILITY

More volatile component -- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

Less volatile component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Majority of components -- Expected to be inherently biodegradable

Atmospheric Oxidation:

More volatile component -- Expected to degrade rapidly in air

BIOACCUMULATION POTENTIAL

Majority of components -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

SECTION 13

DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable

Product Name: GASOLINE, UNLEADED AUTOMOTIVE

Revision Date: 03 Sep 2020

Page 13 of 16

laws and regulations, and material characteristics at time of disposal.

DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

REGULATORY DISPOSAL INFORMATION

RCRA Information: Disposal of unused product may be subject to RCRA regulations (40 CFR 261). Disposal of the used product may also be regulated due to ignitability, corrosivity, reactivity or toxicity as determined by the Toxicity Characteristic Leaching Procedure (TCLP). Potential RCRA characteristics: IGNITABILITY. TCLP (BENZENE)

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14

TRANSPORT INFORMATION

LAND (DOT)

Proper Shipping Name: GASOLINE

Hazard Class & Division: 3

ID Number: 1203

Packing Group: II

Marine Pollutant: Yes

ERG Number: 128

Label(s): 3

Transport Document Name: UN1203, GASOLINE, 3, PG II, MARINE POLLUTANT

LAND (TDG)

Proper Shipping Name: GASOLINE

Hazard Class & Division: 3

UN Number: 1203

Packing Group: II

Special Provisions: 17, 88, 98, 150

SEA (IMDG)

Proper Shipping Name: MOTOR SPIRIT or GASOLINE or PETROL

Hazard Class & Division: 3

EMS Number: F-E, S-E

UN Number: 1203

Packing Group: II

Marine Pollutant: Yes

Label(s): 3

Transport Document Name: UN1203, MOTOR SPIRIT or GASOLINE or PETROL, 3, PG II, (-40°C c.c.), MARINE POLLUTANT

Product Name: GASOLINE, UNLEADED AUTOMOTIVE
Revision Date: 03 Sep 2020
Page 14 of 16

AIR (IATA)

Proper Shipping Name: MOTOR SPIRIT or GASOLINE or PETROL
Hazard Class & Division: 3
UN Number: 1203
Packing Group: II
Label(s) / Mark(s): 3
Transport Document Name: UN1203, GASOLINE, 3, PG II

SECTION 15	REGULATORY INFORMATION
------------	------------------------

OSHA HAZARD COMMUNICATION STANDARD: This material is considered hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200.

Listed or exempt from listing/notification on the following chemical inventories: AIC, DSL, ENCS, KECI, PICCS, TSCA

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302

CERCLA: This material is not subject to any special reporting under the requirements of the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA). Contact local authorities to determine if other reporting requirements apply.

SARA (311/312) REPORTABLE GHS HAZARD CLASSES: Aspiration Hazard, Carcinogenicity, Flammable (gases, aerosols, liquids, or solids), Germ cell mutagenicity, Skin Corrosion or Irritation, Specific Target Organ toxicity (single or repeated exposure)

SARA (313) TOXIC RELEASE INVENTORY:

Chemical Name	CAS Number	Typical Value
BENZENE	71-43-2	<= 1.65%
ETHYL BENZENE	100-41-4	1 - 5%
N-HEXANE	110-54-3	1 - 5%
NAPHTHALENE	91-20-3	<1%
PSEUDOCUMENE (1,2,4-TRIMETHYLBENZENE)	95-63-6	1 - 5%
TOLUENE	108-88-3	5 - 10%
XYLENES	1330-20-7	5 - 10%

The following ingredients are cited on the lists below:

Chemical Name	CAS Number	List Citations
BENZENE	71-43-2	1, 2, 4, 10, 11, 13, 15, 16, 17, 18, 19
ETHYL ALCOHOL	64-17-5	1, 4, 13, 16, 17, 18
ETHYL BENZENE	100-41-4	1, 4, 10, 13, 16, 17, 18, 19
GASOLINE	86290-81-5	1, 18
N-HEXANE	110-54-3	1, 4, 13, 16, 17, 18, 19
NAPHTHALENE	91-20-3	1, 4, 10, 17, 19
PSEUDOCUMENE (1,2,4-	95-63-6	1, 13, 16, 17, 18, 19

Product Name: GASOLINE, UNLEADED AUTOMOTIVE

Revision Date: 03 Sep 2020

Page 15 of 16

TRIMETHYLBENZENE)		
TOLUENE	108-88-3	1, 4, 11, 13, 15, 16, 17, 18, 19
TRIMETHYL BENZENE	25551-13-7	1, 13, 16, 17, 18
XYLENES	1330-20-7	1, 4, 13, 15, 16, 17, 18, 19

--REGULATORY LISTS SEARCHED--

1 = ACGIH ALL	6 = TSCA 5a2	11 = CA P65 REPRO	16 = MN RTK
2 = ACGIH A1	7 = TSCA 5e	12 = CA RTK	17 = NJ RTK
3 = ACGIH A2	8 = TSCA 6	13 = IL RTK	18 = PA RTK
4 = OSHA Z	9 = TSCA 12b	14 = LA RTK	19 = RI RTK
5 = TSCA 4	10 = CA P65 CARC	15 = MI 293	

Code key: CARC=Carcinogen; REPRO=Reproductive

SECTION 16

OTHER INFORMATION



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov. Chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm are created by the combustion of this product.

This warning is given to comply with California Health and Safety Code 25249.6 and does not constitute an admission or a waiver of rights.

N/D = Not determined, N/A = Not applicable

KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

H224: Extremely flammable liquid and vapor; Flammable Liquid, Cat 1
H225: Highly flammable liquid and vapor; Flammable Liquid, Cat 2
H226: Flammable liquid and vapor; Flammable Liquid, Cat 3
H228(2): Flammable solid; Flammable Solid, Cat 2
H302: Harmful if swallowed; Acute Tox Oral, Cat 4
H303: May be harmful if swallowed; Acute Tox Oral, Cat 5
H304: May be fatal if swallowed and enters airways; Aspiration, Cat 1
H312: Harmful in contact with skin; Acute Tox Dermal, Cat 4
H315: Causes skin irritation; Skin Corr/Irritation, Cat 2
H319(2A): Causes serious eye irritation; Serious Eye Damage/Irr, Cat 2A
H320(2B): Causes eye irritation; Serious Eye Damage/Irr, Cat 2B
H332: Harmful if inhaled; Acute Tox Inh, Cat 4
H335: May cause respiratory irritation; Target Organ Single, Resp Irr
H336: May cause drowsiness or dizziness; Target Organ Single, Narcotic
H340(1B): May cause genetic defects; Germ Cell Mutagenicity, Cat 1B
H350(1A): May cause cancer; Carcinogenicity, Cat 1A
H350(1B): May cause cancer; Carcinogenicity, Cat 1B
H351: Suspected of causing cancer; GHS Carcinogenicity, Cat 2
H361(F): Suspected of damaging fertility; Repro Tox, Cat 2 (Fertility)
H372: Causes damage to organs through prolonged or repeated exposure; Target Organ, Repeated, Cat 1
H373: May cause damage to organs through prolonged or repeated exposure; Target Organ, Repeated, Cat 2
H400: Very toxic to aquatic life; Acute Env Tox, Cat 1
H401: Toxic to aquatic life; Acute Env Tox, Cat 2
H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1
H411: Toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 2

Product Name: GASOLINE, UNLEADED AUTOMOTIVE

Revision Date: 03 Sep 2020

Page 16 of 16

H412: Harmful to aquatic life with long lasting effects; Chronic Env Tox, Cat 3

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Hazard Identification: HMIS Flammability information was modified.

Hazard Identification: NFPA Flammability information was modified.

Section 01: Alternate Product Names Table information was added.

Section 04: First Aid Inhalation information was modified.

Section 06: Accidental Release - Spill Management - Land information was modified.

Section 16: HCode Key information was modified.

Section 16: Materials Covered information was deleted.

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

Internal Use Only

MHC: 1A, 0B, 0, 0, 4, 1

PPEC: CF

DGN: 2000316XUS (1011203)

Copyright 2002 Exxon Mobil Corporation, All rights reserved